














Dati Tecnici - Specifications

											
	cond	comp. W	ABS. W	Fuse	Kwh/100Kg	I/ h	kg	Lbs	kg	Lbs	Ton CO2 equiv.
M402 A		4360	2100	16	13.1	19.0	88	194	106	234	4,94
M402 W		4360	1900	16	10.6	210	83	183	101	223	2,55

24h Produzione Ghiaccio - Ice Production

Raffreddamento ad aria - Air Cooled Unit






Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	360	395	420	430
50°	794	871	926	948
21°	340	370	390	400
70°	750	816	860	882
32°	280	305	312	320
90°	617	672	688	705
38°	225	250	257	265
100°	496	551	567	584

Raffreddamento ad acqua - Water Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	315	347	365	370
50°	694	765	805	816
21°	300	332	350	355
70°	661	732	772	783
32°	280	315	327	335
90°	617	694	721	739
38°	270	305	317	325
100°	595	672	699	716



PANNELLO DI CONTROLLO - CONTROL PANEL

	Alimentazione Powered
	In Funzionamento Operating
	Deposito Pieno/Lavaggio Storage Full / Washing
	Allarme Alarm
	Allarme Alta Pressione High Pressure Alarm
	Pulsante Reset/Lavaggio Button Reset/Washing




DIMENSIONI - DIMENSIONS

LxPxH(mm): 760 x 620 x 725
WxDxH(in): 29 15/16" x 24 7/16" x 28 9/16"

DEPOSITO - SLOPE BIN

D205 - D255 - D305(KM305)
D405 (KFM404) - D505 (KFM505)

TIPO GHIACCIO - ICE TYPE

	HALF-LARGE 10 x 29 x 24 - 6 gr 555 PZ. / CICLO PCS / CYCLE
	DICE 22 x 22 x 24 - 10 gr 342 PZ. / CICLO PCS / CYCLE
	LARGE 29 x 29 x 24 - 17 gr 210 PZ. / CICLO PCS / CYCLE

CONDIZIONI USO-OPERATING REQUIREMENTS




220-240V / 1 / 50HZ R404A GWP=3922


MIN	MAX
10°C (50°F)	40°C (104°F)
5°C (41°F)	35°C (95°F)
- 10 %	+ 10 %
1 BAR (14 PSI)	5 BAR (70 PSI)

Calore espulso - Rejected Heat **4559 W**
Volume aria - Air Volume **1180 m³/h**


Vista frontale
Front view




Vista laterale
Lateral view




Vista superiore
Top view



AIR COOLED 



WATER COOLED 



- A** Water drain Ø20 mm
- B** Potable water inlet 3/4 GAS
- C** Electrical cable supply
- D** Water cooled inlet 3/4 GAS
- E** Water cooled outlet 3/4 GAS